TECHNICAL DATA SHEET

# OKBE10482

3 Ply 330 1/4in x 1/16in HR400°F
330 PIW

ORIONTEK
ENGINEERING GOOD SOLUTIONS

## 01 CONSTRUCTION

| | | | |
|---|---|---|---|
| **TOP COVER** | Compound | | **Black EPDM** |
| | Thickness | **1/4** in. | *6.35 mm* |
| | Surface | | **Smooth** |
| | Colour | | **Black** |
| **CARCASS** | Fabric | | **Poly/Nylon** |
| | Number of plies | | **3** |
| **BOTTOM** | Compound | | **Black EPDM** |
| | Thickness | **1/16** in. | *1.59 mm* |
| | Surface | | **Smooth** |


## 02 TECHNICAL SPECIFICATIONS

| | | | | |
|---|---|---|---|---|
| Overall gauge | **15/32** | in. | *11.91* | *mm* |
| Unit weight | **0.2190** | lb/PIW | | |
| Tension rating | **330** | PIW | *57.7* | *N/mm* |
| Temperature — minimum (1) | **–20** | °F | *–29* | *°C* |
| Temperature — maximum (1) | **400** | °F | *204* | *°C* |

## 03 MINIMUM PULLEY DIAMETER (2)

| | | | | |
|---|---|---|---|---|
| ■ Head pulley @ 80–100% tension | **18.00** | in. | *457.20* | *mm* |
| ■ Head pulley @ 60–79% tension | **16.00** | in. | *406.40* | *mm* |
| ■ Head pulley @ ≤59% tension | **12.00** | in. | *304.80* | *mm* |
| ■ Tail pulley | **12.00** | in. | *304.80* | *mm* |





■ **TOP COVER** black · smooth
□ **3-PLY POLY/NYLON** poly/nylon
□ **BOTTOM COVER** smooth · drive side

CROSS-SECTION — NOT TO SCALE

**GAUGE 15/32 IN. / 11.91 MM**

## 04 PROPERTIES

| | |
|---|---|
| High heat | **YES** |

## 05 SPLICING & FASTENERS

| | |
|---|---|
| Splice process | **Step Hot** |
| Step size | **8.00 in.** |
| Plate / rivet fastener | **#190/R6** |
| Hinged fastener | **#550** |

**Oriontek service:** supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

**NOTES** (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek. All values are nominal.

**DISCLAIMER** Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.