TECHNICAL DATA SHEET

OKBE10767

2 DNFP 05/LB2 IM M

Oil resistant · Fire resistant

ORIONTEK


ENGINEERING GOOD SOLUTIONS


01 CONSTRUCTION

TOP COVER	Surface	**Matte**
	Hardness	**87 Shore A Shore A**
BOTTOM	Surface	**Impregnated**

02 TECHNICAL SPECIFICATIONS

Overall gauge	**0.0590**	in.	*1.50*	*mm*
Unit weight	**0.3200**	lb/PIW		
Pull for 1% elongation	**80**	lbs/in.	*14*	*N/mm*
Temperature — minimum (1)	**14**	°F	*-10*	*°C*
Temperature — maximum (1)	**176**	°F	*80*	*°C*
Max. production width	**118**	in.	*2997*	*mm*





SOLID — ONE LAYER
matte

CROSS-SECTION — NOT TO SCALE

GAUGE 0.0590 IN. / 1.50 MM

03 PROPERTIES

Oil resistant	**YES**
Fire resistant	**YES**

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek. All values are nominal.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.