TECHNICAL DATA SHEET

# OKBE10812

2 Ply Poly CR46 Petrol Green PVC C x Bare AS

ORIONTEK
ENGINEERING GOOD SOLUTIONS

## 01 CONSTRUCTION


| | | | | |
|---|---|---|---|---|
| TOP COVER | Compound | | | **Petrol Green PVC** |
| | Thickness | **0.0196** | in. | *0.50 mm* |
| | Surface | | | **Gloss** |
| | Hardness | | | **80 Shore A** |
| CARCASS | Number of plies | | | **2** |
| | Skim between plies | | | **PVC** |
| | Cross rigid | | | **Yes** |
| BOTTOM | Compound | | | **Polyester** |
| | Surface | | | **Bare** |


## 02 TECHNICAL SPECIFICATIONS

| | | | | |
|---|---|---|---|---|
| Overall gauge | **0.0787** | in. | *2.00* | *mm* |
| Unit weight | **0.0358** | lb/PIW | | |
| Pull for 1% elongation | **46** | lbs/in. | *8* | *N/mm* |
| Temperature — minimum (1) | **5** | °F | *−15* | *°C* |
| Temperature — maximum (1) | **176** | °F | *80* | *°C* |
| Max. production width | **118** | in. | *2997* | *mm* |

## 03 MINIMUM PULLEY DIAMETER (2)

| | | | | |
|---|---|---|---|---|
| ■ Normal flex | **1.1811** | in. | *30.00* | *mm* |
| ■ Back flex | **1.9685** | in. | *50.00* | *mm* |






CROSS-SECTION — NOT TO SCALE

**GAUGE 0.0787 IN. / 2.00 MM**

## 04 PROPERTIES

| | |
|---|---|
| Antistatic | **YES** |
| Cross rigid | **YES** |

## 05 SPLICING & FASTENERS

| | |
|---|---|
| Splice process | **Finger** |
| Release foil | **Yes** |

**Oriontek service:** supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

**NOTES** (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek. All values are nominal.

**DISCLAIMER** Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.