TECHNICAL DATA SHEET

OKBE3RAF282

PVC conveyor belt · Petrol glossy · 4.9 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**PVC 85 Shore A (2.00mm)**
	Surface	**Glossy**
	Colour	**Petrol**
CARCASS	Fabric	**Polyester Fabric**
	Number of plies	**3ply**
BOTTOM	Material	**Polyester**
	Surface	**Rigid, Antistatic fabric**

02 TECHNICAL SPECIFICATIONS

Total thickness	**4.9**	mm	*0.193*	*in.*
Weight			**6.0 kg/m²**	
Load at 1% elongation	**15.0**	N/mm	*85.7*	*lbs/in.*
Elongation			**Standard 0.5%, max. 1.0%**	
Temperature — minimum (1)	**–10**	°C	*14*	*°F*
Temperature — maximum (1)	**90**	°C	*194*	*°F*
Max. production width	**3000**	mm	*118*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**100**	mm	*3.94*	*in.*
■ Back-flex (counter-bending) pulley	**180**	mm	*7.09*	*in.*





CROSS-SECTION — NOT TO SCALE

TOTAL 4.9 MM / IN.

04 PROPERTIES

Antistatic	**YES**

05 APPLICATION

Tensile strength 240 N/mm. Max. allowable tension 15.0 N/mm. Elongation at break 20 %. Max. length 100m. Splice: Finger. Features: Oil and Grease Resistant. Typical uses: Heavy duty applications; General purpose conveying; For applications in the tile and brick industry; Oil and grease resistant.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.