TECHNICAL DATA SHEET

OKBEBW-SIDEWALL-ONLY

2-ply black standard rubber sidewall base belt · Black smooth


ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Black standard rubber**
	Surface	**Smooth**
	Colour	**Black**
CARCASS	Fabric	**Polyester/nylon (EP) tension plies, cross-rigid plies**
	Number of plies	**2**
BOTTOM	Material	**Black standard rubber**
	Surface	**Smooth**
	Colour	**Black**

02 TECHNICAL SPECIFICATIONS

Working tension	**220** PIW	*38.5 N/mm*





RUBBER COVER
black · smooth

2-PLY POLYESTER
polyester/nylon (ep) tension

RUBBER COVER
black · smooth · drive side

CROSS-SECTION — NOT TO SCALE

03 APPLICATION

Belt 2-ply 220 PIW black standard 1/8 x 1/16 in. Widths 24, 30 and 36 in. Sidewall 2-1/2 or 3 in tall, flush to belt edge. Min. pulley 10 in.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.

SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US