TECHNICAL DATA SHEET

OKBEBWX-ST-SC

Sbr, or, fr or hr rubber sidewall base belt · Black smooth

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**SBR, OR, FR or HR rubber**
	Surface	**Smooth**
	Colour	**Black**
CARCASS	Fabric	**Polyester/nylon (EP) tension plies, cross-rigid plies**
	Number of plies	**Steel cord + steel breaker**
BOTTOM	Material	**SBR, OR, FR or HR rubber**
	Surface	**Smooth**
	Colour	**Black**





SBR COVER black · smooth

1-PLY POLYESTER polyester/nylon (ep) tension

SBR COVER black · smooth · drive side

CROSS-SECTION — NOT TO SCALE

03 APPLICATION

Steel cord tension member ST1600 to ST4000 with steel breaker cross-rigid plies for high vertical lifts. Special order.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.

SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US