TECHNICAL DATA SHEET

OKBEBWX3332MI

Sbr, mor or hr rubber sidewall base belt · Black smooth


ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**SBR, MOR or HR rubber**
	Surface	**Smooth**
	Colour	**Black**
CARCASS	Fabric	**Polyester/nylon (EP) tension plies, cross-rigid plies**
	Number of plies	**3 + 2**
BOTTOM	Material	**SBR, MOR or HR rubber**
	Surface	**Smooth**
	Colour	**Black**

02 TECHNICAL SPECIFICATIONS

Working tension	**330** PIW	*57.7 N/mm*





CROSS-SECTION — NOT TO SCALE

03 APPLICATION

Three EP tension plies with two monofilament / fiberglass cross-rigid plies. Stocked in SBR, MOR and HR.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.