TECHNICAL DATA SHEET

OKBEBWX4442MI

Sbr rubber sidewall base belt · Black smooth


ORIONTEK
ENGINEERING GOOD SOLUTIONS


01 CONSTRUCTION

TOP COVER	Material	**SBR rubber**
	Surface	**Smooth**
	Colour	**Black**
CARCASS	Fabric	**Polyester/nylon (EP) tension plies, cross-rigid plies**
	Number of plies	**4 + 2**
BOTTOM	Material	**SBR rubber**
	Surface	**Smooth**
	Colour	**Black**

02 TECHNICAL SPECIFICATIONS

Working tension	**440** PIW	*77.0 N/mm*





CROSS-SECTION — NOT TO SCALE

03 APPLICATION

Four EP tension plies with two monofilament / fiberglass cross-rigid plies. Stocked in SBR.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.