TECHNICAL DATA SHEET

OKBECFTG-60FS-45

PU aramid cord belt · Blue rough pattern · 4.5 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	TPU
	Surface	Rough pattern
	Colour	Blue
CARCASS	Fabric	Aramid Cord
BOTTOM	Material	NBR
	Surface	Rough pattern
	Colour	Blue

02 TECHNICAL SPECIFICATIONS

Total thickness	4.5 mm	0.177 in.
Weight	4.9 kg/m²	
Elongation	Standard 0.5%, max. 1.0%	
Temperature — minimum (1)	−10 °C	14 °F
Temperature — maximum (1)	60 °C	140 °F

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	110 mm	4.33 in.





PU COVER — blue · rough pattern
ARAMID CORD CORE — aramid cord
NITRILE COVER — blue · rough pattern · drive

CROSS-SECTION — NOT TO SCALE

TOTAL 4.5 MM / IN.

04 PROPERTIES

Antistatic	YES

05 APPLICATION

Tensile strength 700 N/mm. Elongation at break 3.5 %. Max. length 1,000~160,000 mm. Splice: Finger splice, (10×200). Typical uses: Live roller conveyor.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.