TECHNICAL DATA SHEET

OKBEKSG-250

Polyamide power transmission belt · Green nbr-impreg. fabric · 0.85 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Polyamide**
	Surface	**NBR-impreg. fabric**
	Colour	**Green**
CARCASS	Fabric	**Polyamide Film 0.2mm**
BOTTOM	Material	**Special nonwoven fabric**
	Colour	**White**

02 TECHNICAL SPECIFICATIONS

Total thickness	**0.85** mm	*0.033 in.*
Weight	**0.8 kg/m²**	
Elongation	**Standard 2.0%, max. 3.0%**	
Temperature – minimum (1)	**–20** °C	*–4 °F*
Temperature – maximum (1)	**80** °C	*176 °F*
Max. production width	**305** mm	*12 in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**25** mm	*0.98 in.*





FABRIC TOP FACE nbr-impreg. fabric · green
PA FILM CORE polyamide film 0.2mm
FELT COVER white · drive side

CROSS-SECTION – NOT TO SCALE — **TOTAL 0.85 MM / IN.**

04 APPLICATION

Tensile strength 60N/mm. Max. allowable tension 9.0N/mm. Elongation at break 20%. Max. length 105m. Splice: Skiver. Features: Twist resistance, Abrasion resistance. Typical uses: Spindle tape.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.