TECHNICAL DATA SHEET

OKBERT-300

Nitrile rough top belt · Blue rough top · .7 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**NBR**
	Surface	**Rough top**
	Colour	**Blue**
CARCASS	Fabric	**Polyester Fabric**
	Number of plies	**3ply**
BOTTOM	Material	**Polyester**
	Surface	**Fabric**
	Colour	**White**

02 TECHNICAL SPECIFICATIONS

Total thickness	**.7**	mm	*0.028*	*in.*
Weight			**6.5 kg/m²**	
Load at 1% elongation	**12.0**	N/mm	*68.5*	*lbs/in.*
Elongation			**Standard 0.5%, max. 1.0%**	
Temperature – minimum (1)	**–20**	°C	*–4*	*°F*
Temperature – maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**600**	mm	*24*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**100**	mm	*3.94*	*in.*





NITRILE COVER blue · rough top
3-PLY POLYESTER polyester fabric
FABRIC DRIVE FACE fabric · drive side

CROSS-SECTION – NOT TO SCALE — **TOTAL .7 MM / IN.**

04 PROPERTIES

Antistatic	**YES**

05 APPLICATION

Tensile strength 290N/mm. Max. allowable tension 12.0N/mm. Elongation at break 15%. Max. length 42m. Splice: Skiver, Mechanical lacing. Features: Cushioning property, High grip, Superior abrasion resistance, Incline conveyance, Slider bed, Roller bed. Typical uses: Flexo folder gluer; Woodworking machine; Corrugating machine (Cut off).

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.