TECHNICAL DATA SHEET

OKBESE-A-WN-F

Rubber food-grade seamless belt · White flat · 8.0 mm
Antistatic · FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Rubber**
	Surface	**Flat**
	Colour	**White**
CARCASS	Fabric	**Polyester Cord**

02 TECHNICAL SPECIFICATIONS

Total thickness	**8.0** mm	*0.315 in.*
Weight	**8.0 kg/m²**	
Elongation	**Standard 0.5%, max. 0.5~1.0%**	
Temperature — minimum (1)	**−20** °C	*−4 °F*
Temperature — maximum (1)	**60** °C	*140 °F*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**80** mm	*3.15 in.*





☐ **RUBBER COVER** white · flat
☐ **POLYESTER CORD CORE** polyester cord
☐ **FABRIC DRIVE FACE** fabric · drive side

CROSS-SECTION — NOT TO SCALE — **TOTAL 8.0 MM / IN.**

04 PROPERTIES

Antistatic	**YES**
FDA compliant compound	**YES**

05 APPLICATION

Tensile strength 58.8N/mm. Elongation at break 10%. Max. length 400~1970mm. Splice: Seamless. Features: High grip, Cushioning property, Keep conveyed goods clean. Typical uses: Feeder belt.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.

SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US