TECHNICAL DATA SHEET

OKBESG-750-2P

Polyamide power transmission belt · flat · 1.1 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Polyamide film**
	Surface	**Flat**
CARCASS	Fabric	**Polyamide Film 0.75mm**
BOTTOM	Material	**Polyamide**
	Surface	**NBR-impreg. fabric**
	Colour	**Green**

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.1**	mm	*0.043*	*in.*
Weight			**1.2 kg/m²**	
Elongation			**Standard 1.0%, max. 3.0%**	
Temperature – minimum (1)	**–20**	°C	*–4*	*°F*
Temperature – maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**300**	mm	*12*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**75**	mm	*2.95*	*in.*





POLYAMIDE COVER
flat

PA FILM CORE
polyamide film 0.75mm

FABRIC DRIVE FACE
nbr-impreg. fabric · drive s

CROSS-SECTION – NOT TO SCALE

TOTAL 1.1 MM / IN.

04 APPLICATION

Tensile strength 225N/mm. Max. allowable tension 33.6N/mm. Elongation at break 20%. Max. length 105m. Splice: Skiver. Features: Slider bed, Roller bed. Typical uses: Can manufacturing machine; Light duty conveyor; Printing press.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.

SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US