TECHNICAL DATA SHEET

OKBESLA-8E14

Nitrile machine tape · Blue taffeta pattern · 1.4 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	NBR
	Surface	Taffeta pattern
	Colour	Blue
CARCASS	Fabric	Polyester Fabric
BOTTOM	Material	NBR
	Surface	Taffeta pattern
	Colour	Blue





NITRILE COVER
blue · taffeta pattern

1-PLY POLYESTER
polyester fabric

NITRILE COVER
blue · taffeta pattern · dri

CROSS-SECTION — NOT TO SCALE

TOTAL 1.4 MM / IN.

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.4**	mm	*0.055*	*in.*
Weight			**1.7 kg/m²**	
Elongation			**Standard 1.0%, max. 2.0%**	
Temperature — minimum (1)	**−20**	°C	*−4*	*°F*
Temperature — maximum (1)	**60**	°C	*140*	*°F*
Max. production width	**500**	mm	*20*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**25**	mm	*0.98*	*in.*
■ Back-flex (counter-bending) pulley	**25**	mm	*0.98*	*in.*

04 PROPERTIES

Antistatic	YES

05 APPLICATION

Tensile strength 90N/mm. Max. allowable tension 18N/mm. Elongation at break 13%. Max. length 100m. Splice: Finger, (10×70, 5×35). Features: Whisper, Roller bed. Typical uses: Bookbinding machine; Light duty transmission; Right angle transfer / RAT; Postal machine.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.