TECHNICAL DATA SHEET

OKBETAIR-350

Nitrile power transmission belt · Green rough pattern · 1.15 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**NBR (0.2mm)**
	Surface	**Rough pattern**
	Colour	**Green**
CARCASS	Fabric	**Polyamide Film 0.35mm**
BOTTOM	Material	**Polyamide**
	Surface	**Fabric**
	Colour	**Blue**

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.15**	mm	*0.045*	*in.*
Weight			**1.2 kg/m²**	
Elongation			**Standard 1.0%, max. 3.0%**	
Temperature — minimum (1)	**–20**	°C	*–4*	*°F*
Temperature — maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**320**	mm	*13*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**30**	mm	*1.18*	*in.*





NITRILE COVER green · rough pattern
PA FILM CORE polyamide film 0.35mm
FABRIC DRIVE FACE fabric · drive side

CROSS-SECTION — NOT TO SCALE

TOTAL 1.15 MM / IN.

04 PROPERTIES

Antistatic	**YES**

05 APPLICATION

Tensile strength 105N/mm. Max. allowable tension 15.6N/mm. Elongation at break 20%. Max. length 100m. Splice: Skiver. Features: Slider bed. Typical uses: Paper converting belt for printing application; Book making machine; Table supporting conveyor.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.