TECHNICAL DATA SHEET

OKBETTP-8E18N

Special polyamide machine tape · Purple fabric · 1.8 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION


TOP COVER	Material	**Special polyamide**
	Surface	**Fabric**
	Colour	**Purple**
CARCASS	Fabric	**Polyester Fabric**
BOTTOM	Material	**Special polyamide**
	Surface	**Fabric**
	Colour	**White**


02 TECHNICAL SPECIFICATIONS

Total thickness	**1.8**	mm	*0.071*	*in.*
Weight			**1.8 kg/m²**	
Elongation			**Standard 1.0%, max. 2.0%**	
Temperature – minimum (1)	**–20**	°C	*–4*	*°F*
Temperature – maximum (1)	**60**	°C	*140*	*°F*
Max. production width	**500**	mm	*20*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**40**	mm	*1.57*	*in.*
■ Back-flex (counter-bending) pulley	**40**	mm	*1.57*	*in.*





FABRIC TOP FACE
fabric · purple

1-PLY POLYESTER
polyester fabric

FABRIC DRIVE FACE
fabric · drive side

CROSS-SECTION – NOT TO SCALE

TOTAL 1.8 MM / IN.

04 PROPERTIES

Antistatic	**YES**

05 APPLICATION

Tensile strength 140N/mm. Max. allowable tension 18.0N/mm. Elongation at break 13%. Max. length 100m. Splice: Finger(10×70, 5×35), In cases where elongation is, less than 1%, 10×30 is applicable. Features: Superior abrasion resistance, High lateral rigidity, Slider bed, Roller bed. Typical uses: Printing press; Light duty conveyor.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.