TECHNICAL DATA SHEET

OKCHN1269

Food-grade conveyor belt · Blue
FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Colour	**Blue**
CARCASS	Fabric	**Polyester fabric**

02 TECHNICAL SPECIFICATIONS

Weight			**0.12 lb/ft²**	
Temperature — minimum (1)	**−15**	°C	*5*	*°F*
Temperature — maximum (1)	**70**	°C	*158*	*°F*
Max. production width	**5000**	mm	*197*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**80**	mm	*3.15*	*in.*
■ Back-flex (counter-bending) pulley	**80**	mm	*3.15*	*in.*





□ **FABRIC TOP FACE** — blue
□ **1-PLY POLYESTER** — polyester fabric
□ **FABRIC DRIVE FACE** — fabric · drive side

CROSS-SECTION — NOT TO SCALE

04 PROPERTIES

FDA compliant compound	**YES**

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.