TECHNICAL DATA SHEET

OKCHN1595

nitrile conveyor belt · Red gp · 7.00 mm
Medium-friction conveying surface · Metal-detectable

ORIONTEK
ENGINEERING GOOD SOLUTIONS

Manufactured in Europe to Oriontek specification. Supplied, fabricated and installed by Oriontek.

01 CONSTRUCTION

CONVEYING

Material		**Synthetic elastomer (NBR)**
Thickness	**4.50** mm	*0.177 in.*
Surface pattern		**GP**
Colour		**Red**
Coefficient of friction		**MF — medium friction**

DRIVING

Material		**Mesh, polyester**
Thickness	**2.50** mm	*0.098 in.*

02 TECHNICAL SPECIFICATIONS

Total thickness	**7.00**	mm	*0.28*	*in.*
Weight	**8.00**	kg/m²	*1.63*	*lbs/sq.ft*
Elongation at 1%	**13**	N/mm	*74.0*	*lbs/in.*
Max. admissible pull	**13**	N/mm	*74.0*	*lbs/in.*
Temperature — minimum [1]	**-20**	°C	*-4*	*°F*
Temperature — maximum [1]	**100**	°C	*212*	*°F*
Max. production width [3]	**1000**	mm	*39*	*in.*

03 MINIMUM RADIUS / DIAMETER [2]

Bending roller, min. diameter	**80**	mm	*3.15*	*in.*
Counter-bending roller, min. dia.	**100**	mm	*3.94*	*in.*

04 FRICTION — DRIVING SURFACE

Raw steel sheet	**0.30** [-]
Laminated plastic / wood	**0.35** [-]
Steel roller	**0.25** [-]
Rubberized roller	**0.35** [-]





05 PERFORMANCE & HANDLING

Humidity influence	NO
Suitable for metal detector	YES
Permanently antistatic, dynamic (UNI EN ISO 21179)	NO
Static conductivity (UNI EN ISO 284)	NO
Conveying on skid bed	YES
Conveying on rollers	YES
Skid bed on top *and* return	NO
Troughed conveying	NO
Curved conveyor	NO
Swan-neck conveying	YES
Inclined conveying	YES
Accumulation belts	NO
Chemical resistance rating	8

06 COMPLIANCE

- REACH EC 1907/2006 and amendments

07 APPROVED APPLICATIONS

- Corrugated cardboard
- Wood industry

Notes: Fast splicing without presses, fasteners or glues

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES [1] Operating the belt at its limit values may reduce service life. [2] Minimum radius and diameter values depend on the joint type specified by Oriontek. [3] Maximum production width 1000 mm / 39 in.; wider widths require prior authorization.

DISCLAIMER Values are laboratory results measured at +23 °C and 50% relative humidity. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.