TECHNICAL DATA SHEET

OKCHN2628

2-ply TPO food-grade conveyor belt · Blue matt · 1.10 mm
Low-friction conveying surface · Metal-detectable · Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

Manufactured in Europe to Oriontek specification. Supplied, fabricated and installed by Oriontek.

01 CONSTRUCTION

CONVEYING	Material			**Thermoplastic Polyolefin (TPO)**
	Thickness	**0.20** mm	*0.008* *in.*	
	Surface pattern			**Matt**
	Colour			**Blue**
	Coefficient of friction			**LF — low friction**
CARCASS	Material			**Polyester (PET)**
	Number of plies			**2**
	Weft type			**Combined**
DRIVING	Material			**Fabric, polyolefin (TPO) impregnated**
	Surface pattern			**Fabric**
	Colour			**Transparent**

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.10**	mm	*0.04*	*in.*
Weight	**1.00**	kg/m²	*0.20*	*lbs/sq.ft*
Elongation at 1%	**4**	N/mm	*23.0*	*lbs/in.*
Max. admissible pull	**8**	N/mm	*46.0*	*lbs/in.*
Temperature — minimum (1)	**–40**	°C	*–40*	*°F*
Temperature — maximum (1)	**80**	°C	*176*	*°F*
Max. production width (3)	**1600**	mm	*63*	*in.*

03 MINIMUM RADIUS / DIAMETER (2)

■ Knife edge, minimum radius	**3**	mm	*0.12*	*in.*
■ Bending roller, min. diameter	**6**	mm	*0.24*	*in.*
■ Counter-bending roller, min. dia.	**16**	mm	*0.63*	*in.*

04 FRICTION — DRIVING SURFACE

■ Raw steel sheet	**0.20** [-]
■ Laminated plastic / wood	**0.25** [-]
■ Steel roller	**0.20** [-]
■ Rubberized roller	**0.30** [-]





TPO COVER — blue · matt
2-PLY POLYESTER — polyester (pet)
FABRIC DRIVE FACE — fabric · drive side

CROSS-SECTION — NOT TO SCALE

TOTAL 1.10 MM / 0.04 IN.

05 PERFORMANCE & HANDLING

Humidity influence	NO
Suitable for metal detector	YES
Permanently antistatic, dynamic (UNI EN ISO 21179)	YES
Static conductivity (UNI EN ISO 284)	NO
Conveying on skid bed	YES
Conveying on rollers	YES
Skid bed on top *and* return	NO
Troughed conveying	YES
Curved conveyor	YES
Swan-neck conveying	NO
Inclined conveying	NO
Accumulation belts	NO
Chemical resistance rating	12

06 COMPLIANCE

- REACH EC 1907/2006 and amendments
- EC 1935/2004 and amendments
- EC 2023/2006 and amendments
- EU 10/2011, 2024/3190 and amendments
- FDA — U.S. Food and Drug Administration

07 APPROVED APPLICATIONS

- Food — confectionery
- Food — chocolate bars
- Food — dairy
- Food — poultry
- Food — bakery
- Food — chocolate cooling tunnel
- Food — meat and fish processing
- Food — seafood processing

Notes: Maximum production width 1600 mm. Requests for production in wider widths must be authorized by Technical Management

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.