TECHNICAL DATA SHEET

OKCHN49

2-ply PVC conveyor belt · Black smooth · 1.80 mm
Low-friction conveying surface · Flame retardant · Antistatic


ORIONTEK
ENGINEERING GOOD SOLUTIONS

Manufactured in Europe to Oriontek specification. Supplied, fabricated and installed by Oriontek.

01 CONSTRUCTION

CONVEYING	Material			PVC 70 Sh.A (±5)
	Thickness	0.30	mm	0.012 in.
	Surface pattern			Smooth
	Colour			Black
	Coefficient of friction			LF — low friction
CARCASS	Material			Polyester (PET)
	Number of plies			2
	Weft type			Combined
DRIVING	Material			Fabric, polyurethane (TPU) impregnated
	Surface pattern			LdB fabric
	Colour			White





PVC COVER — black · smooth
2-PLY POLYESTER — polyester (pet)
FABRIC DRIVE FACE — ldb fabric · drive side

CROSS-SECTION — NOT TO SCALE

TOTAL 1.80 MM / 0.07 IN.

02 TECHNICAL SPECIFICATIONS

Total thickness	1.80	mm	0.07	in.
Weight	2.00	kg/m²	0.41	lbs/sq.ft
Elongation at 1%	6	N/mm	34.0	lbs/in.
Max. admissible pull	12	N/mm	69.0	lbs/in.
Temperature — minimum (1)	−10	°C	14	°F
Temperature — maximum (1)	60	°C	140	°F
Max. production width (3)	3000	mm	118	in.

03 MINIMUM RADIUS / DIAMETER (2)

■ Bending roller, min. diameter	20	mm	0.79	in.
■ Counter-bending roller, min. dia.	25	mm	0.98	in.

04 FRICTION — DRIVING SURFACE

■ Raw steel sheet	0.20 [-]
■ Laminated plastic / wood	0.25 [-]
■ Steel roller	0.20 [-]
■ Rubberized roller	0.30 [-]

05 PERFORMANCE & HANDLING

Humidity influence	NO
Suitable for metal detector	NO
Permanently antistatic, dynamic (UNI EN ISO 21179)	YES
Static conductivity (UNI EN ISO 284)	NO
Conveying on skid bed	YES
Conveying on rollers	YES
Skid bed on top *and* return	NO
Troughed conveying	YES
Curved conveyor	YES
Swan-neck conveying	NO
Inclined conveying	NO
Accumulation belts	YES
Chemical resistance rating	2

06 COMPLIANCE

- REACH EC 1907/2006 and amendments
- Flame Retardant UL94HB Horizontal Burning

07 APPROVED APPLICATIONS

- Textile — inspecting machines
- Packaging
- Materials handling
- Paper industry — tissue
- Supermarkets check-outs

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum radius and diameter values depend on the joint type specified by Oriontek. (3) Maximum production width 3000 mm / 118 in.; wider widths require prior authorization.
DISCLAIMER Values are laboratory results measured at +23 °C and 50% relative humidity. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.