TECHNICAL DATA SHEET


OKESA12G2K


PVC conveyor belt · Green 00 pattern g2

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material		**PVC**
	Thickness	**3.70** mm	*0.146 in.*
	Surface		**Pattern G2**
	Colour		**Green 00**
	Hardness		**65 Shore A**
CARCASS	Fabric		**Polyester fabric**
BOTTOM	Material		**PVC**
	Thickness	**0.70** mm	*0.028 in.*
	Surface		**Pattern K**
	Colour		**Green 00**





CROSS-SECTION — NOT TO SCALE

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.