TECHNICAL DATA SHEET

OKESA21ZK


PVC food-grade conveyor belt · White pattern z
FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material		PVC
	Thickness	2.00 mm	*0.079 in.*
	Surface		Pattern Z
	Colour		White
	Hardness		70 Shore A
CARCASS	Fabric		Polyester fabric
BOTTOM	Material		PVC
	Thickness	0.70 mm	*0.028 in.*
	Surface		Pattern K
	Colour		White





☐ PVC COVER
white · pattern z

☐ 1-PLY POLYESTER
polyester fabric

☐ PVC COVER
white · pattern k · drive si

CROSS-SECTION — NOT TO SCALE

03 PROPERTIES

FDA compliant compound	YES
EU food contact	YES

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.