TECHNICAL DATA SHEET

# OKESC07UFMT

Polyurethane (pu) food-grade conveyor belt · White mat
FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

## 01 CONSTRUCTION

| | | | |
|---|---|---|---|
| TOP COVER | Material | | **Polyurethane (PU)** |
| | Thickness | **0.30** mm | *0.012 in.* |
| | Surface | | **Mat** |
| | Colour | | **White** |
| | Hardness | | **86 Shore A** |
| CARCASS | Fabric | | **Polyester fabric** |
| BOTTOM | Surface | | **Woven polyester** |
| | Colour | | **Natural** |





☐ **PU COVER** — white · mat
☐ **1-PLY POLYESTER** — polyester fabric
☐ **FABRIC DRIVE FACE** — woven polyester · drive side

CROSS-SECTION — NOT TO SCALE

## 03 PROPERTIES

| | |
|---|---|
| FDA compliant compound | **YES** |
| EU food contact | **YES** |

**Oriontek service:** supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

**NOTES** (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

**DISCLAIMER** Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.