TECHNICAL DATA SHEET

OKESH12Y1R

PVC conveyor belt · Green 23 pattern y1
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material		HPVC
	Thickness	0.60 mm	0.024 in.
	Surface		Pattern Y1
	Colour		Green 23
	Hardness		75 Shore A
CARCASS	Fabric		Polyester fabric
BOTTOM	Material		CR
	Thickness	0.10 mm	0.004 in.
	Surface		Impregn.
	Colour		Black 00





PVC COVER — green 23 · pattern y1
1-PLY POLYESTER — polyester fabric
CR COVER — black 00 · impregn. · drive

CROSS-SECTION — NOT TO SCALE

03 PROPERTIES

Antistatic	YES

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.