TECHNICAL DATA SHEET


OKFO800015


Chrome leather flat belt / machine tape · Grey leather · 3 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Chrome leather**
	Surface	**Leather**
	Colour	**Grey**
CARCASS	Fabric	**Polyamide sheet, highly-orientated**
BOTTOM	Material	**Chrome leather**
	Surface	**Leather**
	Colour	**Grey**





LEATHER COVER
grey · leather

1-PLY POLYAMIDE
polyamide sheet, highly-orie

LEATHER COVER
grey · leather · drive side

CROSS-SECTION — NOT TO SCALE

TOTAL 3 MM / 0.118 IN.

02 TECHNICAL SPECIFICATIONS

Total thickness	**3**	mm	*0.118*	*in.*
Weight			**0.604 lb/ft²**	
Load at 1% elongation	**3**	N/mm	*17.1*	*lbs/in.*
Temperature — minimum (1)	**–40**	°C	*–40*	*°F*
Temperature — maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**500**	mm	*20*	*in.*
Coefficient of friction			**Top 0.4 / drive side 0.4**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**35**	mm	*1.38*	*in.*
■ Back-flex (counter-bending) pulley	**35**	mm	*1.38*	*in.*

04 PROPERTIES

Antistatic	**YES**
Troughed conveying	**NO**

05 APPLICATION

Yarn (Power transmission belt (half-cross power transmission belt))

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.