TECHNICAL DATA SHEET

OKFO822058

Elastomer g flat belt / machine tape · Green normal texture · 3 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Elastomer G**
	Surface	**Normal texture**
	Colour	**Green**
CARCASS	Fabric	**Polyester fabric, highly flexible**
BOTTOM	Material	**Mixed fabric**
	Surface	**Fabric**
	Colour	**Black**

02 TECHNICAL SPECIFICATIONS


Total thickness	**3**	mm	*0.118*	*in.*
Weight			**0.655 lb/ft²**	
Load at 1% elongation	**10**	N/mm	*57.1*	*lbs/in.*
Temperature — minimum (1)	**–20**	°C	*–4*	*°F*
Temperature — maximum (1)	**70**	°C	*158*	*°F*
Max. production width	**1000**	mm	*39*	*in.*
Coefficient of friction			**Top 1.1 / drive side 0.3**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**40**	mm	*1.57*	*in.*
■ Back-flex (counter-bending) pulley	**40**	mm	*1.57*	*in.*







ELASTOMER COVER green · normal texture
1-PLY POLYESTER polyester fabric, highly fle
FABRIC DRIVE FACE fabric · drive side

CROSS-SECTION — NOT TO SCALE

TOTAL 3 MM / 0.118 IN.

04 PROPERTIES

Antistatic	**YES**
Troughed conveying	**NO**

05 APPLICATION

Distribution Parcel, Carrier, Sores (Live Roller conveyor); Packaging (Box folding machines); Paper Manufacturing, Packaging (Carrier belt for paper and packaging); Printing (Folders rotogravure printing (TRR); Post press (trimmers, 3-knife trimmers)); Wood Based Panel Industry (Pick-off belt)

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.