TECHNICAL DATA SHEET

OKFO822081

Elastomer g flat belt / machine tape · Green fine texture · 1.3 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Elastomer G**
	Surface	**Fine texture**
	Colour	**Green**
CARCASS	Fabric	**Mixed fabric, highly flexible**
BOTTOM	Material	**Mixed fabric**
	Surface	**Fabric**
	Colour	**Black**

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.3**	mm	*0.051*	*in.*
Weight			**0.287 lb/ft²**	
Load at 1% elongation	**4**	N/mm	*22.8*	*lbs/in.*
Temperature – minimum (1)	**–20**	°C	*–4*	*°F*
Temperature – maximum (1)	**70**	°C	*158*	*°F*
Max. production width	**1320**	mm	*52*	*in.*
Coefficient of friction			**Top 1.1 / drive side 0.3**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**14**	mm	*0.55*	*in.*
■ Back-flex (counter-bending) pulley	**14**	mm	*0.55*	*in.*







ELASTOMER COVER
green · fine texture

1-PLY MIXED FABRIC,
mixed fabric, highly flexibl

FABRIC DRIVE FACE
fabric · drive side

CROSS-SECTION – NOT TO SCALE

TOTAL 1.3 MM / 0.051 IN.

04 PROPERTIES

Antistatic	YES
Troughed conveying	NO

05 APPLICATION

Packaging (Box folding machines); Paper Manufacturing (Cross-cutters (paper, cardboard, plastic film); Paper bags, plastic bags: pick-off belt; Tissue industry); Paper Manufacturing, Packaging (Carrier belt for paper and packaging); Printing (Automatic labellers; Folders newspaper (coldset); Folders rotogravure printing (TRR); Folders web offset printing / heatset (ORR); Post press (compensating stackers, bundlers);

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.