TECHNICAL DATA SHEET

OKFO822139

Polyamide flat belt / machine tape · White fabric · 1.8 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Polyamide fabric**
	Surface	**Fabric**
	Colour	**White**
CARCASS	Fabric	**Polyester fabric, highly flexible**
BOTTOM	Material	**Polyamide fabric**
	Surface	**Fabric**
	Colour	**White**

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.8**	mm	*0.071*	*in.*
Weight			**0.399 lb/ft²**	
Load at 1% elongation	**7.5**	N/mm	*42.8*	*lbs/in.*
Temperature – minimum (1)	**–20**	°C	*–4*	*°F*
Temperature – maximum (1)	**70**	°C	*158*	*°F*
Max. production width	**1000**	mm	*39*	*in.*
Coefficient of friction			**Top 0.2 / drive side 0.2**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**30**	mm	*1.18*	*in.*
■ Back-flex (counter-bending) pulley	**30**	mm	*1.18*	*in.*





FABRIC TOP FACE
fabric · white

1-PLY POLYESTER
polyester fabric, highly fle

FABRIC DRIVE FACE
fabric · drive side

CROSS-SECTION – NOT TO SCALE

TOTAL 1.8 MM / 0.071 IN.

04 PROPERTIES

Antistatic	**YES**
Troughed conveying	**NO**
Accumulation conveying	**YES**

05 APPLICATION

Printing (Folders rotogravure printing (TRR))

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.