TECHNICAL DATA SHEET

OKFO822151

Medium grip flat belt / machine tape · Grey fine texture · 1.35 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Medium Grip**
	Surface	**Fine texture**
	Colour	**Grey**
CARCASS	Fabric	**Mixed fabric, highly flexible**
BOTTOM	Material	**MediumGrip**
	Surface	**Fine texture**
	Colour	**Grey**

02 TECHNICAL SPECIFICATIONS


Total thickness	**1.35**	mm	*0.053*	*in.*
Weight			**0.287 lb/ft²**	
Load at 1% elongation	**2**	N/mm	*11.4*	*lbs/in.*
Temperature – minimum (1)	**–20**	°C	*–4*	*°F*
Temperature – maximum (1)	**70**	°C	*158*	*°F*
Max. production width	**1200**	mm	*47*	*in.*
Coefficient of friction			**Top 1.6 / drive side 1.6**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**14**	mm	*0.55*	*in.*
■ Back-flex (counter-bending) pulley	**14**	mm	*0.55*	*in.*







■ **MEDIUM GRIP COVER** grey · fine texture
□ **1-PLY MIXED FABRIC,** mixed fabric, highly flexibl
■ **MEDIUMGRIP COVER** grey · fine texture · drive

CROSS-SECTION – NOT TO SCALE — **TOTAL 1.35 MM / 0.053 IN.**

04 PROPERTIES

Troughed conveying	NO
Accumulation conveying	NO

05 APPLICATION

Packaging (Packaging machines); Paper Manufacturing (Cross-cutters (paper, cardboard, plastic film); Tissue industry); Paper Manufacturing, Packaging (Carrier belt for paper and packaging); Postal (Letter sorting machines); Printing (Folders newspaper (coldset); Newspaper printing (coldset); Post press (compensating stackers, bundlers); Post press (saddle stitchers); Sheet-fed printing (folding machines, sheet feeder

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.