TECHNICAL DATA SHEET

OKFO822155

Medium grip food-grade flat belt / machine tape · Grey normal texture · 6 mm
Antistatic · FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Medium Grip**
	Surface	**Normal texture**
	Colour	**Grey**
CARCASS	Fabric	**Polyester fabric, highly flexible**
BOTTOM	Material	**MediumGrip**
	Surface	**Normal texture**
	Colour	**Grey**

02 TECHNICAL SPECIFICATIONS


Total thickness	**6**	mm	*0.236*	*in.*
Weight			**1.362 lb/ft²**	
Load at 1% elongation	**11.5**	N/mm	*65.7*	*lbs/in.*
Temperature – minimum (1)	**–20**	°C	*–4*	*°F*
Temperature – maximum (1)	**70**	°C	*158*	*°F*
Max. production width	**1000**	mm	*39*	*in.*
Coefficient of friction			**Top 1.6 / drive side 1.6**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**60**	mm	*2.36*	*in.*
■ Back-flex (counter-bending) pulley	**60**	mm	*2.36*	*in.*







MEDIUM GRIP COVER grey · normal texture
1-PLY POLYESTER polyester fabric, highly fle
MEDIUMGRIP COVER grey · normal texture · driv

CROSS-SECTION – NOT TO SCALE

TOTAL 6 MM / 0.236 IN.

04 PROPERTIES

Antistatic	**YES**
FDA compliant compound	**YES**
Troughed conveying	**NO**
Accumulation conveying	**NO**

05 APPLICATION

Packaging (Box folding machines; FlexoFolderGluer FFG (corrugated): folder gluer belt); Paper Manufacturing (Tube winders; Winding paper, unwinding paper); Wood Based Panel Industry (Board conveying)

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.