TECHNICAL DATA SHEET

OKFO850042

Polyamide flat belt / machine tape · Green fabric · 1.15 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Polyamide fabric**
	Surface	**Fabric**
	Colour	**Green**
CARCASS	Fabric	**Polyamide fabric, highly flexible**
BOTTOM	Material	**Polyamide fabric**
	Surface	**Fabric**
	Colour	**Green**

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.15**	mm	*0.045*	*in.*
Weight			**0.184 lb/ft²**	
Load at 1% elongation	**3**	N/mm	*17.1*	*lbs/in.*
Temperature – minimum (1)	**–20**	°C	*–4*	*°F*
Temperature – maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**1500**	mm	*59*	*in.*
Coefficient of friction			**Top 0.2 / drive side 0.2**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**30**	mm	*1.18*	*in.*
■ Back-flex (counter-bending) pulley	**30**	mm	*1.18*	*in.*





FABRIC TOP FACE fabric · green
1-PLY POLYAMIDE polyamide fabric, highly fle
FABRIC DRIVE FACE fabric · drive side

CROSS-SECTION – NOT TO SCALE — **TOTAL 1.15 MM / 0.045 IN.**

04 PROPERTIES

Antistatic	YES
Troughed conveying	NO
Accumulation conveying	YES

05 APPLICATION

Paper Manufacturing (Cross-cutters (paper, cardboard, plastic film)); Paper Manufacturing, Packaging (Carrier belt for paper and packaging); Printing (Folders newspaper (coldset); Folders web offset printing / heatset (ORR); Post press (compensating stackers, bundlers)); Yarn (Ring spinning frames)

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.