TECHNICAL DATA SHEET

OKFO855503

Polyester flat belt / machine tape · Grey velveteen · 1.5 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION


TOP COVER	Material	**Polyester web**
	Surface	**Velveteen**
	Colour	**Grey**
CARCASS	Fabric	**Polyurethane, elastic**
BOTTOM	Material	**Polyamide**
	Surface	**Fine texture**
	Colour	**Green**


02 TECHNICAL SPECIFICATIONS


Total thickness	**1.5**	mm	*0.059*	*in.*
Weight			**0.266 lb/ft²**	
Load at 1% elongation	**0.75**	N/mm	*4.3*	*lbs/in.*
Temperature — minimum (1)	**–20**	°C	*–4*	*°F*
Temperature — maximum (1)	**60**	°C	*140*	*°F*
Max. production width	**1350**	mm	*53*	*in.*
Coefficient of friction			**Top 0.2 / drive side 0.8**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**14**	mm	*0.55*	*in.*
■ Back-flex (counter-bending) pulley	**14**	mm	*0.55*	*in.*







FABRIC TOP FACE
velveteen · grey

1-PLY PU
polyurethane, elastic

FABRIC DRIVE FACE
fine texture · drive side

CROSS-SECTION — NOT TO SCALE

TOTAL 1.5 MM / 0.059 IN.

04 PROPERTIES

Antistatic	**YES**
Troughed conveying	NO
Accumulation conveying	NO

05 APPLICATION

Packaging (Packaging machines); Paper Manufacturing (Cross-cutters for sensitive paper quality); Paper Manufacturing, Packaging (Carrier belt for paper and packaging); Postal (Letter sorting machines; Letter sorting machines (discharge belt, stacker)); Printing (Post press (compensating stackers, bundlers); Sheet-fed printing (folding machines, sheet feeders, sheet dischargers))

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.