TECHNICAL DATA SHEET

# OKFO900045

2-ply polyvinyl chloride conveyor belt · Green smooth · 2.79 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

## 01 CONSTRUCTION


| | | |
|---|---|---|
| TOP COVER | Material | **Polyvinyl chloride** |
| | Surface | **Smooth** |
| | Colour | **Green** |
| | Hardness | **66 Shore A** |
| CARCASS | Fabric | **Polyester fabric** |
| | Number of plies | **2** |
| BOTTOM | Material | **Polyurethane impregnation** |
| | Surface | **Fabric** |
| | Colour | **Transparent** |


## 02 TECHNICAL SPECIFICATIONS

| | | |
|---|---|---|
| Total thickness | **2.79** mm | *0.11 in.* |
| Weight | **0.70 lb/ft²** | |
| Load at 1% elongation | **10.5** N/mm | *60 lbs/in.* |
| Lateral stiffness | **Exceptionally laterally stiff** | |
| Running noise | **Low noise** | |

## 03 MINIMUM PULLEY DIAMETER (2)

| | | |
|---|---|---|
| ■ Minimum pulley / nose bar | **61** mm | *2.4 in.* |
| ■ Back-flex (counter-bending) pulley | **61** mm | *2.4 in.* |






CROSS-SECTION — NOT TO SCALE

**TOTAL 2.79 MM / 0.11 IN.**

## 04 PROPERTIES

| | |
|---|---|
| Antistatic | **YES** |
| Troughed conveying | NO |
| Accumulation conveying | NO |
| Curved conveyor | NO |

**Oriontek service:** supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

**NOTES** (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

**DISCLAIMER** Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.