TECHNICAL DATA SHEET

OKFO907049

2-ply polyurethane food-grade conveyor belt · White matte · 1.78 mm
FDA compliant compound · Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	Polyurethane
	Surface	Matte
	Colour	White
	Hardness	92 Shore A
CARCASS	Fabric	Polyester fabric
	Number of plies	2
BOTTOM	Material	Polyurethane impregnation
	Surface	Fabric
	Colour	Transparent

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.78** mm	*0.07 in.*
Weight		**0.40 lb/ft²**
Load at 1% elongation	**5.1** N/mm	*29 lbs/in.*
Lateral stiffness		**Laterally stiff**
Running noise		**Normal**

03 MINIMUM PULLEY DIAMETER (2)

Minimum pulley / nose bar		**On request**
■ Back-flex (counter-bending) pulley	**25** mm	*1.0 in.*





CROSS-SECTION — NOT TO SCALE

TOTAL 1.78 MM / 0.07 IN.

04 PROPERTIES

FDA compliant compound	YES
Antistatic	YES
Troughed conveying	NO
Accumulation conveying	YES
Curved conveyor	NO

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.