TECHNICAL DATA SHEET

OKFO908201

2-ply styrene butadiene rubber conveyor belt · Black light impression · 3.58 mm
Flame retardant

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Styrene butadiene rubber**
	Surface	**Light impression**
	Colour	**Black**
CARCASS	Fabric	**Fabric of polyester filament warp and monofilament weft**
	Number of plies	**2**
BOTTOM	Material	**Resorcinol formaldehyde latex impregnation**
	Surface	**Fabric**
	Colour	**Black**


02 TECHNICAL SPECIFICATIONS

Total thickness	**3.58**	mm	*0.141*	*in.*
Weight			**0.88 lb/ft²**	
Load at 1% elongation	**4.73**	N/mm	*27.0*	*lbs/in.*
Working tension	**90**	PIW	*15.7*	*N/mm*
Temperature – minimum [1]	**–29**	°C	*–20*	*°F*
Temperature – maximum [1]	**107**	°C	*225*	*°F*
Max. production width	**1829**	mm	*72*	*in.*
Coefficient of friction			**Top 0.8 / drive side 0.16**	
Lateral stiffness			**Laterally stiff**	
Running noise			**Normal**	

03 MINIMUM PULLEY DIAMETER [2]

■ Minimum pulley / nose bar	**89**	mm	*3.50*	*in.*
■ Back-flex (counter-bending) pulley	**127**	mm	*5.00*	*in.*





CROSS-SECTION – NOT TO SCALE — **TOTAL 3.58 MM / 0.141 IN.**

04 PROPERTIES

Flame retardant	**YES**
Troughed conveying	NO
Accumulation conveying	NO
Curved conveyor	NO

05 APPLICATION

Airport logistics (Tray conveyor); Automotive (Press-in-feed/inter-press conveyors); Building material industry (Brick conveying / Tiles conveying / Stone); transport; Food industry (Transport of packed food in freezers); General material handling (Horizontal conveying); Logistics (Acceleration conveyor; Braking conveyor;); Parcel handling; Telescopic conveyor; Tire/Rubber (Quality control / storage; Rubber extrusion

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES [1] Operating the belt at its limit values may reduce service life. [2] Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.