TECHNICAL DATA SHEET

OKF0995207

Polyurethane flat belt / machine tape · Green smooth · 1 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION


TOP COVER	Material	**Polyurethane**
	Surface	**Smooth**
	Colour	**Green**
CARCASS	Fabric	**Polyurethane, elastic**
BOTTOM	Material	**Polyurethane**
	Surface	**Coarse texture**
	Colour	**Black**


02 TECHNICAL SPECIFICATIONS

Total thickness	**1**	mm	*0.039*	*in.*
Weight			**0.215 lb/ft²**	
Load at 1% elongation	**0.32**	N/mm	*1.8*	*lbs/in.*
Temperature — minimum (1)	**–20**	°C	*–4*	*°F*
Temperature — maximum (1)	**60**	°C	*140*	*°F*
Max. production width	**550**	mm	*22*	*in.*
Coefficient of friction			**Top 1.5 / drive side 0.6**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**14**	mm	*0.55*	*in.*
■ Back-flex (counter-bending) pulley	**14**	mm	*0.55*	*in.*





PU COVER
green · smooth

1-PLY PU
polyurethane, elastic

PU COVER
black · coarse texture · dri

CROSS-SECTION — NOT TO SCALE

TOTAL 1 MM / 0.039 IN.

04 PROPERTIES

Antistatic	YES
Troughed conveying	YES
Accumulation conveying	NO

05 APPLICATION

Paper Manufacturing, Packaging (Carrier belt for paper and packaging); Printing (Post press (compensating stackers, bundlers); Sheet-fed printing (folding machines, sheet feeders, sheet dischargers))

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.