TECHNICAL DATA SHEET

OKFO995381

Polyamide flat belt / machine tape · White fabric · 0.7 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Polyamide fabric**
	Surface	**Fabric**
	Colour	**White**
CARCASS	Fabric	**Polyamide fabric, highly flexible**
BOTTOM	Material	**Polyurethane**
	Surface	**Matte**
	Colour	**Green**

02 TECHNICAL SPECIFICATIONS

Total thickness	**0.7**	mm	*0.028*	*in.*
Weight			**0.102 lb/ft²**	
Load at 1% elongation	**2.5**	N/mm	*14.3*	*lbs/in.*
Temperature — minimum (1)	**–20**	°C	*–4*	*°F*
Temperature — maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**1500**	mm	*59*	*in.*
Coefficient of friction			**Top 0.2 / drive side 1**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**14**	mm	*0.55*	*in.*
■ Back-flex (counter-bending) pulley	**14**	mm	*0.55*	*in.*





FABRIC TOP FACE
fabric · white

1-PLY POLYAMIDE
polyamide fabric, highly fle

PU COVER
green · matte · drive side

CROSS-SECTION — NOT TO SCALE

TOTAL 0.7 MM / 0.028 IN.

04 PROPERTIES

Antistatic	**YES**
Troughed conveying	NO
Accumulation conveying	NO

05 APPLICATION

Yarn (Ring spinning frames)

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.