TECHNICAL DATA SHEET

OKHB328DD

3-ply cotton (co) conveyor belt · Beige fabric · 4.4 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Cotton (CO)**
	Surface	**Fabric**
	Colour	**Beige**
CARCASS	Fabric	**Cotton (CO)**
	Number of plies	**3**
BOTTOM	Material	**Cotton (CO)**
	Surface	**Fabric**
	Colour	**Beige**


02 TECHNICAL SPECIFICATIONS

Total thickness	**4.4**	mm	*0.173*	*in.*
Weight			**3.3 kg/m²**	
Load at 1% elongation	**2.2**	N/mm	*12.6*	*lbs/in.*
Temperature — minimum (1)	**–40**	°C	*–40*	*°F*
Temperature — maximum (1)	**100**	°C	*212*	*°F*
Max. production width	**2000**	mm	*79*	*in.*
Coefficient of friction			**Drive side on steel 0.15**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**100**	mm	*3.94*	*in.*
■ Back-flex (counter-bending) pulley	**100**	mm	*3.94*	*in.*





FABRIC TOP FACE — fabric · beige
3-PLY COTTON — cotton (co)
FABRIC DRIVE FACE — fabric · drive side

CROSS-SECTION — NOT TO SCALE

TOTAL 4.4 MM / IN.

04 PROPERTIES

EU 10/2011	**YES**
Slider bed	**YES**
Roller bed	**YES**

05 APPLICATION

Features: Easy release. Typical uses: Food processing/conveying belt, Transport of hot rubber. Industries: Bread, Rubber industry. Admissible tensile force 5.5 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.