TECHNICAL DATA SHEET

# OKHBA120COS-B

1-ply PVC conveyor belt · Black smooth · 3.4 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

## 01 CONSTRUCTION

| | | |
|---|---|---|
| TOP COVER | Material | **PVC** |
| | Surface | **Smooth** |
| | Colour | **Black** |
| CARCASS | Fabric | **Polyester (PET)** |
| | Number of plies | **1** |
| BOTTOM | Material | **Polyester fabric (PET) impregnated with polyvinylchloride** |
| | Surface | **Fabric** |
| | Colour | **Black** |


## 02 TECHNICAL SPECIFICATIONS

| | | | | |
|---|---|---|---|---|
| Total thickness | **3.4** | mm | *0.134* | *in.* |
| Weight | | | **4.1 kg/m²** | |
| Load at 1% elongation | **7** | N/mm | *40.0* | *lbs/in.* |
| Temperature — minimum (1) | **–23** | °C | *–9* | *°F* |
| Temperature — maximum (1) | **82** | °C | *180* | *°F* |
| Max. production width | **1829** | mm | *72* | *in.* |
| Coefficient of friction | | | **Drive side on steel 0.20** | |

## 03 MINIMUM PULLEY DIAMETER (2)

| | | | | |
|---|---|---|---|---|
| ■ Minimum pulley / nose bar | **79** | mm | *3.11* | *in.* |
| ■ Back-flex (counter-bending) pulley | **79** | mm | *3.11* | *in.* |





**PVC COVER** black · smooth
**1-PLY POLYESTER** polyester (pet)
**FABRIC DRIVE FACE** fabric · drive side

CROSS-SECTION — NOT TO SCALE — **TOTAL 3.4 MM / IN.**

## 04 PROPERTIES

| | |
|---|---|
| Flame retardant | YES |
| Slider bed | YES |
| Roller bed | YES |

## 05 APPLICATION

Features: Temperature variation resistant. Typical uses: Decline belt, Incline belt. Industries: Distribution centers. Admissible tensile force 16 N/mm.

**Oriontek service:** supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

**NOTES** (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

**DISCLAIMER** Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.


SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US