TECHNICAL DATA SHEET

OKHBA150COS-LS-B

1-ply PVC conveyor belt · Black smooth · 3.8 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**PVC**
	Surface	**Smooth**
	Colour	**Black**
CARCASS	Fabric	**Polyester (PET)**
	Number of plies	**1**
BOTTOM	Material	**Polyester fabric (PET) impregnated with polyvinylchloride (PVC)**
	Surface	**Impregnated fabric**
	Colour	**Black**

02 TECHNICAL SPECIFICATIONS

Total thickness	**3.8**	mm	*0.150*	*in.*
Weight			**4.8 kg/m²**	
Temperature — minimum (1)	**–23**	°C	*–9*	*°F*
Temperature — maximum (1)	**82**	°C	*180*	*°F*
Max. production width	**1524**	mm	*60*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**102**	mm	*4.02*	*in.*
■ Back-flex (counter-bending) pulley	**102**	mm	*4.02*	*in.*





■ PVC COVER
black · smooth

□ 1-PLY POLYESTER
polyester (pet)

□ FABRIC DRIVE FACE
impregnated fabric · drive s

CROSS-SECTION — NOT TO SCALE

TOTAL 3.8 MM / IN.

04 PROPERTIES

Metal detector friendly	YES
Slider bed	YES
Roller bed	YES
Troughed	YES

05 APPLICATION

Features: Oil resistant, Temperature variation resistant. Typical uses: Packaging belt, Processing belt. Industries: Distribution centers, General conveying, Various industries. Admissible tensile force 26 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.