TECHNICAL DATA SHEET

OKHBA155COS-W

1-ply PVC food-grade conveyor belt · White smooth · 3.9 mm
FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**PVC**
	Surface	**Smooth**
	Colour	**White**
CARCASS	Fabric	**Polyester (PET)**
	Number of plies	**1**
BOTTOM	Material	**Polyester fabric (PET) impregnated with polyvinylchloride**
	Surface	**Fabric**
	Colour	**White**


02 TECHNICAL SPECIFICATIONS

Total thickness	**3.9**	mm	*0.154*	*in.*
Weight			**4.8 kg/m²**	
Load at 1% elongation	**11**	N/mm	*62.8*	*lbs/in.*
Temperature – minimum (1)	**–23**	°C	*–9*	*°F*
Temperature – maximum (1)	**82**	°C	*180*	*°F*
Max. production width	**1524**	mm	*60*	*in.*
Coefficient of friction			**Drive side on steel 0.15**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**89**	mm	*3.50*	*in.*
■ Back-flex (counter-bending) pulley	**102**	mm	*4.02*	*in.*





□ **PVC COVER** white · smooth
□ **1-PLY POLYESTER** polyester (pet)
□ **FABRIC DRIVE FACE** fabric · drive side

CROSS-SECTION – NOT TO SCALE — **TOTAL 3.9 MM / IN.**

04 PROPERTIES

FDA compliant compound	**YES**
Slider bed	**YES**
Roller bed	**YES**

05 APPLICATION

Features: Oil resistant, Temperature variation resistant. Typical uses: Packaging belt. Industries: Fruit, Primary food packaging, Vegetables. Admissible tensile force 27 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.

SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US