TECHNICAL DATA SHEET

OKHBBVT585B-1150

1-ply meta-aramid fabric conveyor belt · Off-white fabric · 2.0 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Meta-aramid fabric**
	Surface	**Fabric**
	Colour	**Off-white**
CARCASS	Fabric	**Meta-aramid fabric**
	Number of plies	**1**
BOTTOM	Material	**Meta-aramid fabric**
	Surface	**Fabric**
	Colour	**Off-white**


02 TECHNICAL SPECIFICATIONS

Total thickness	**2.0**	mm	*0.079*	*in.*
Weight			**0.95 kg/m²**	
Temperature — minimum (1)	**–18**	°C	*0*	*°F*
Temperature — maximum (1)	**204**	°C	*399*	*°F*
Max. production width	**292**	mm	*11*	*in.*
Coefficient of friction			**Drive side on steel 0.15**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**25**	mm	*0.98*	*in.*
■ Back-flex (counter-bending) pulley	**25**	mm	*0.98*	*in.*





FABRIC TOP FACE — fabric · off-white
1-PLY ARAMID — meta-aramid fabric
FABRIC DRIVE FACE — fabric · drive side

CROSS-SECTION — NOT TO SCALE

TOTAL 2.0 MM / IN.

04 PROPERTIES

Metal detector friendly	**YES**
Slider bed	**YES**

05 APPLICATION

Features: Air permeability, Dimensionally stable, High temperature resistant. Industries: Yarn processing.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.