TECHNICAL DATA SHEET

OKHBCNB-6EVWQ-A1


2-ply TPO food-grade conveyor belt · White matt · 1.5 mm
Antistatic · FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	TPO
	Surface	Matt
	Colour	White
CARCASS	Fabric	Polyester (PET)
	Number of plies	2
BOTTOM	Material	TPO
	Surface	Quadrillé (quadrangular) structure
	Colour	White





☐ TPO COVER — white · matt
☐ 2-PLY POLYESTER — polyester (pet)
☐ TPO COVER — white · quadrillé (quadrangu

CROSS-SECTION — NOT TO SCALE — TOTAL 1.5 MM / IN.

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.5**	mm	*0.059*	*in.*
Weight				**1.3 kg/m²**
Load at 1% elongation	**3.0**	N/mm	*17.1*	*lbs/in.*
Temperature — minimum (1)	**–40**	°C	*–40*	*°F*
Temperature — maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**2400**	mm	*94*	*in.*
Coefficient of friction				**Drive side on steel 0.15**

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**40**	mm	*1.57*	*in.*
■ Back-flex (counter-bending) pulley	**50**	mm	*1.97*	*in.*

04 PROPERTIES

Antistatic	YES
FDA compliant compound	YES
EU 10/2011	YES
Halal	YES
Metal detector friendly	YES
Slider bed	YES
Roller bed	YES

05 APPLICATION

Features: Easy cleanability, Easy release, Edges wear resistant, Frayless edges, Hydrolysis resistant, Low friction running side, Reverse side coated. Typical uses: Cooling (line) belt, Decline belt, Dough belt, Enrobing belt, Incline belt, Inspection/control belt, Packaging belt. Industries: Baked snacks, Biscuit and Crackers, Chocolate, Convenience food, Fruit, Pastry, Poultry, Ready meals, Red meat. Admissible tensile force 7 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.