TECHNICAL DATA SHEET

OKHBCT-18-30E

1-ply nitrile power transmission belt · Light gray rough structure · 3.0 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**NBR rubber**
	Surface	**Rough structure**
	Colour	**Light gray**
CARCASS	Fabric	**Polyester (PET)**
	Number of plies	**1**
BOTTOM	Material	**NBR rubber**
	Surface	**Rough structure**
	Colour	**Light gray**


02 TECHNICAL SPECIFICATIONS

Total thickness	**3.0**	mm	*0.118*	*in.*
Weight			**3.0 kg/m²**	
Load at 1% elongation	**18**	N/mm	*102.8*	*lbs/in.*
Temperature – minimum (1)	**0**	°C	*32*	*°F*
Temperature – maximum (1)	**60**	°C	*140*	*°F*
Max. production width	**1200**	mm	*47*	*in.*

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**30**	mm	*1.18*	*in.*
■ Back-flex (counter-bending) pulley	**30**	mm	*1.18*	*in.*





NITRILE COVER light gray · rough structure
1-PLY POLYESTER polyester (pet)
NITRILE COVER light gray · rough structure

CROSS-SECTION – NOT TO SCALE — **TOTAL 3.0 MM / IN.**

04 PROPERTIES

Antistatic	**YES**
Roller bed	**YES**

05 APPLICATION

Features: Abrasion resistant, Adhesive-free joint, Constant coefficient of friction, Dimensionally stable, Longitudinal flexibility, Outstanding flex-fatigue. Typical uses: Folder-gluer belt, Live roller drive belt. Industries: Box making.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.

SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US