TECHNICAL DATA SHEET

OKHBEAB-10YRRS


2-ply silicone conveyor belt · Red glossy · 5.4 mm

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Silicone**
	Surface	**Glossy**
	Colour	**Red**
CARCASS	Fabric	**Nonwoven (PET/PP)**
	Number of plies	**2**
BOTTOM	Material	**Polyester fabric**
	Surface	**Fabric**
	Colour	**White**





CROSS-SECTION — NOT TO SCALE

TOTAL 5.4 MM / IN.

02 TECHNICAL SPECIFICATIONS

Total thickness	**5.4**	mm	*0.213*	*in.*
Weight			**4.6 kg/m²**	
Load at 1% elongation	**9.0**	N/mm	*51.4*	*lbs/in.*
Coefficient of friction			**Drive side on steel 0.15**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**200**	mm	*7.87*	*in.*

04 PROPERTIES

Slider bed	YES
Roller bed	YES

05 APPLICATION

Features: Excellent release, Impact resistant. Typical uses: Transport of hot rubber. Industries: Rubber industry, Tire.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.