TECHNICAL DATA SHEET

OKHBENM-10EHDV

4-ply PVC conveyor belt · Dark green impregnated fabric · 4.3 mm
Antistatic

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	PVC
	Surface	Impregnated fabric
	Colour	Dark green
CARCASS	Fabric	Polyester (PET)
	Number of plies	4
BOTTOM	Material	PVC
	Surface	Matt
	Colour	Dark green

02 TECHNICAL SPECIFICATIONS

Total thickness	**4.3**	mm	*0.169*	*in.*
Weight			**5.0 kg/m²**	
Load at 1% elongation	**6.0**	N/mm	*34.3*	*lbs/in.*
Temperature — minimum (1)	**–10**	°C	*14*	*°F*
Temperature — maximum (1)	**70**	°C	*158*	*°F*
Max. production width	**3000**	mm	*118*	*in.*
Coefficient of friction			**Drive side on steel 0.30**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**60**	mm	*2.36*	*in.*
■ Back-flex (counter-bending) pulley	**60**	mm	*2.36*	*in.*





CROSS-SECTION — NOT TO SCALE — TOTAL 4.3 MM / IN.

04 PROPERTIES

Antistatic	YES
Roller bed	YES

05 APPLICATION

Features: Dimensionally stable, High lateral stability. Typical uses: Vacuum belt. Industries: Textile others. Admissible tensile force 17 N/mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.

SOLUTIONS@ORIONTEK.US · 786-440-6995 · ORIONTEK.US