TECHNICAL DATA SHEET

OKHBERHB1000

Natural rubber power transmission belt · Light green buffed finish

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION


TOP COVER	Material	**Natural rubber**
	Surface	**Buffed finish**
	Colour	**Light green**
CARCASS	Fabric	**Polyamide (PA)**
BOTTOM	Material	**Cross-linked PU**
	Surface	**Smooth**
	Colour	**Black**

02 TECHNICAL SPECIFICATIONS

Coefficient of friction	**Drive side on steel 0.30**

nless Belts
B1000

ions
uer belt



RUBBER COVER light green · buffed finish
1-PLY POLYAMIDE polyamide (pa)
CROSS-LINKED P COVER black · smooth · drive side

CROSS-SECTION — NOT TO SCALE

03 APPLICATION

Features: Abrasion resistant, Abrasion resistant on both sides.
Typical uses: Folder-gluer belt.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.