TECHNICAL DATA SHEET

# OKHBFAC-8EIC

2-ply PU food-grade conveyor belt · Cobalt blue cone top structure · 2.4 mm
FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

## 01 CONSTRUCTION

| | | |
|---|---|---|
| TOP COVER | Material | TPU |
| | Surface | Cone top structure |
| | Colour | Cobalt blue |
| CARCASS | Fabric | Polyester (PET) |
| | Number of plies | 2 |
| BOTTOM | Material | Polyester fabric |
| | Surface | Impregnated fabric |
| | Colour | White |

## 02 TECHNICAL SPECIFICATIONS

| | | | | |
|---|---|---|---|---|
| Total thickness | **2.4** | mm | *0.094* | *in.* |
| Weight | | | **1.7 kg/m²** | |
| Load at 1% elongation | **6.0** | N/mm | *34.3* | *lbs/in.* |
| Temperature – minimum (1) | **–30** | °C | *–22* | *°F* |
| Temperature – maximum (1) | **100** | °C | *212* | *°F* |
| Max. production width | **1000** | mm | *39* | *in.* |
| Coefficient of friction | | | **Drive side on steel 0.15** | |

## 03 MINIMUM PULLEY DIAMETER (2)

| | | | | |
|---|---|---|---|---|
| ■ Minimum pulley / nose bar | **15** | mm | *0.59* | *in.* |
| ■ Back-flex (counter-bending) pulley | **25** | mm | *0.98* | *in.* |






CROSS-SECTION — NOT TO SCALE — TOTAL 2.4 MM / IN.

## 04 PROPERTIES

| | |
|---|---|
| FDA compliant compound | YES |
| EU 10/2011 | YES |
| Metal detector friendly | YES |
| Slider bed | YES |
| Roller bed | YES |

## 05 APPLICATION

Features: Abrasion resistant, High grip surface, Oil and fat resistant. Typical uses: Decline belt, Delivery belt, Food processing/conveying belt, Incline belt. Industries: Dairy (incl. cheese), Poultry, Primary food packaging, Red meat. Admissible tensile force 15 N/mm. Knife-edge radius 4 mm.

**Oriontek service:** supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

**NOTES** (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

**DISCLAIMER** Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.