TECHNICAL DATA SHEET

OKHBFGBB001H04

Natural rubber food-grade power transmission belt · Red buffed finish
FDA compliant compound


ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Natural rubber**
	Surface	**Buffed finish**
	Colour	**Red**
CARCASS	Fabric	**Polyester (PET) fabric**
BOTTOM	Material	**Neoprene**
	Colour	**Black**

nless Belts
B001H04

ions
elt, Folder-gluer belt



RUBBER COVER
red · buffed finish

1-PLY POLYESTER
polyester (pet) fabric

NEOPRENE COVER
black · drive side

CROSS-SECTION — NOT TO SCALE

03 PROPERTIES

FDA compliant compound	YES
EU 10/2011	YES

04 APPLICATION

Features: High coefficient of friction surface. Typical uses: Feeder belt, Folder-gluer belt.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.