TECHNICAL DATA SHEET

OKHBFNT-5EC

2-ply polyester food-grade conveyor belt · White fabric · 1.8 mm
FDA compliant compound

ORIONTEK
ENGINEERING GOOD SOLUTIONS

01 CONSTRUCTION

TOP COVER	Material	**Polyester (PET)/Cotton (CO) fabric**
	Surface	**Fabric**
	Colour	**White**
CARCASS	Fabric	**Polyester (PET)/Cotton (CO) fabric**
	Number of plies	**2**
BOTTOM	Material	**Polyester (PET)/Cotton (CO) fabric**
	Surface	**Fabric**
	Colour	**White**

02 TECHNICAL SPECIFICATIONS

Total thickness	**1.8**	mm	*0.071*	*in.*
Weight			**1.6 kg/m²**	
Load at 1% elongation	**3.2**	N/mm	*18.3*	*lbs/in.*
Temperature – minimum (1)	**–30**	°C	*–22*	*°F*
Temperature – maximum (1)	**80**	°C	*176*	*°F*
Max. production width	**2400**	mm	*94*	*in.*
Coefficient of friction			**Drive side on steel 0.15**	

03 MINIMUM PULLEY DIAMETER (2)

■ Minimum pulley / nose bar	**20**	mm	*0.79*	*in.*
■ Back-flex (counter-bending) pulley	**30**	mm	*1.18*	*in.*





FABRIC TOP FACE — fabric · white
2-PLY POLYESTER — polyester (pet)/cotton (co)
FABRIC DRIVE FACE — fabric · drive side

CROSS-SECTION – NOT TO SCALE — **TOTAL 1.8 MM / IN.**

04 PROPERTIES

FDA compliant compound	**YES**
EU 10/2011	**YES**
Metal detector friendly	**YES**
Slider bed	**YES**
Roller bed	**YES**
Low noise	**YES**

05 APPLICATION

Features: Dimensionally stable, Easy release. Typical uses: Dough belt, Food processing/conveying belt. Industries: Biscuit and Crackers, Bread, Pastry. Admissible tensile force 8.0 N/mm. Knife-edge radius 4 mm.

Oriontek service: supplied endless-joined, open-length or fabricated with profiles, sidewalls, cleats and V-guides. Onsite splicing available.

NOTES (1) Operating the belt at its limit values may reduce service life. (2) Minimum pulley diameters depend on belt tension and on the splice or fastener specified by Oriontek.

DISCLAIMER Values are nominal. They describe the product as tested and do not necessarily reflect conditions of industrial use, nor do they guarantee suitability for a specific application. The customer remains responsible for correct selection and use. Oriontek cannot be held liable for damages arising from use of this product. Specifications may be revised without prior notice.